

Wind Tower Lift

SL25-WT



24 m/min




200 m



250 kg



0,75m x 0,55m



2



Technical specification

SL25-WT

Load capacity (kg / pax)	250 / 2
Maximum height (m)	200 (*)
Maximum tie distance (m)	4 (*)
Mast section (m x m x m - kg)	1,9 x 0,08 x 0,42 - 23
Rack module	6
Rated power (kW)	2 x 1,5
Power supply	400V 3P+PE 50/60Hz
Control voltage (V)	48

(*) For higher values contact us

Features

- Two geared motor brake
- Two centrifugal brakes
- Rack inductive detector
- Emergency stop
- Travel limit switches and emergency l.s.
- Buffers at the travel limits
- Bottom and top trapdoor with l.s.
- Cabin access door with electromechanical interlock
- Low voltage panel
- Phase control relay
- Non-slipping floor
- Cabin roof railing
- Bottom anti-obstacle device
- Lighting inside the cabin
- Anchorage points inside & at cabin roof
- Noise warning device for lift in movement

Optionals

- Maintenance control box
- Overload device
- Top anti-obstacle device
- Landing gates with limit switch
- Cold climate (up to -25°C)



DEALER



Delegación España
Pablo Gorosabel 40, 1B, of. 10
20400 Tolosa, Gipuzkoa | ESPAÑA
T +34 943 056 374

CICLO FAPRIL, S.A.
Rua do Vale do Grou, nº 1378, Apt. 2
3754-908 Aguada da Cima, Águeda | PORTUGAL
T +351 234 660 570 | F +351 234 666 030