

Wind Tower Lift

SL30-WT



18 m/min




200 m



320kg



0,97m x 1m



3



Technical specification

SL30-WT

Load capacity (kg / pax)	320 / 3
Maximum height (m)	200 (*)
Maximum tie distance (m)	3
Mast section (m x m x m - kg)	1,9 x 0,08 x 0,42 - 23
Rack module	6
Rated power (kW)	2 x 1,5
Power supply	400V 3P+PE 50/60Hz
Control voltaje (V)	48

(*) For higher values contact us

Features

- Two geared motor brake with centrifugal brakes
- Rack inductive detector
- Emergency stop
- Travel limit switches and emergency l.s.
- Buffers at the travel limits
- Bottom and top trapdoor with l.s.
- Bottom & top anti-obstacle device
- Cabin access door & window with electromechanical interlock
- Overload device
- Low voltaje panel
- Phase control relay
- Non-slipping floor
- Cabin roof railing
- Lighting inside the cabin
- Anchorage points inside & at cabin roof
- Noise warning device for lift in movement

Optionals

- Maintenance control box
- Landing gates with limit switch
- Cold climate (up to -25°C)
- Offshore installation protection



DEALER



Delegación España
Pablo Gorosabel 40, 1B, of. 10
20400 Tolosa, Gipuzkoa | ESPAÑA
T +34 943 056 374

CICLO FAPRIL, S.A.
Rua do Vale do Grou, nº 1378, Apt. 2
3754-908 Aguada da Cima, Águeda | PORTUGAL
T +351 234 660 570 | F +351 234 666 030